

The scissor lift tables with foot-operated hydraulic pump are the ideal tools for a variety of lifting and loading operations and for use as "work station" to provide improved ergonomic conditions together with improved productivity. Available with 150-800 kg nominal capacity, single and double scissor for elevation up to 1300 mm, they represent the best solution for the manual load handling, combining functioning, cost saving, safety and health of operator during work.





ADVANTAGES

COMPACTNESS



- Depending on the model, the table is equipped with a folding handlebar.
 When fully closed, it becomes very compact and can be stored in a convenient, space saving way.
- Sturdy steel machine designed to transport and pick your goods becoming your reliable partner in the everyday work.
- Easy handling granted by ergonomic handle and the combination of fixed and steering polyurethane wheels.

EASY OF USE



- Thanks to the efficient hydraulic foot pump the table can be brought to the desired height to easily pick or raise working materials.
- With the lever on the handle it is possible to lower the table without clicks with the utmost precision.

SAFETY



- The foot brakes on the steering wheels guarantee perfect stability during operations.
- The practical wheel guards on the steering wheels protect the feet while working.
- The objects raised at an individual and ergonomic height greatly reduce the strain on your back.
- The appropriate inspection supports fix the platform in case of maintenance or cleaning work.



APPLICATION FIELDS

Lift tables are perfect for order preparation and goods mobilization. They are commonly used throughout industry and commerce, including factories, warehouses, retail outlets, printers, schools, colleges, laboratories, banks and offices.

LT Series

DESCRIPTION					
MODEL		LT15	LT30	LT35D	LT80
CAPACITY	Kg	150	300	350	800
MATERIAL		STEEL	STEEL	STEEL	STEEL
SCISSOR TYPE		SINGLE SCISSOR	SINGLE SCISSOR	DOUBLE SCISSOR	SINGLE SCISSOF
PUSH HANDLE TYPE		FOLDING	FOLDING	FIXED	FIXED
NET WEIGHT	Kg	40	74	106	112
HANDLE HEIGHT	mm	880	1010	970	990
PUMPING TIME NO LOAD	n.	19	36	75	53
PUMPING TIME LOADED	n.	23	47	80	61
LIFT					
MIN. HEIGHT	mm	210	280	350	415
MAX. HEIGHT	mm	720	900	1300	1000
LIFTING DISTANCE	mm	510	620	950	585
LIFT FUNCTION		FOOT PEDAL	FOOT PEDAL	FOOT PEDAL	FOOT PEDAL
TABLE SIZE					
HEIGHT	mm	35	50	50	60
WIDTH	mm	450	500	500	510
DEPTH	mm	700	815	905	1016
WHEELS					
WHEELS MATERIAL		POLYURETHANE	POLYURETHANE	POLYURETHANE	POLYURETHANE
WHEELS LOCKING FUNCTION		YES	YES	YES	YES
FIXED WHEELS	n.	2	2	2	2
SWIVEL WHEELS	n.	2	2	2	2
DIAMETER OF THE WHEEL	mm	100	125	125	150

MATERIAL HANDLING EQUIPMENT

Moving, handling and storing your goods

MANUAL OPERATED TRUCKS

Complete range for handling activities









ELECTRIC PALLET TRUCKS

Compact solutions in warehouses





STACKERS

Lifting solutions from light to heavy duty







PR INDUSTRIAL S.R.L.

